## **ASSIGNMENT 3**

Textbook Assignment: "Portable Fire-Fighting and Dewatering Equipment" and "Fire-Fighting Systems," chapters 5 and 6.

**Learning Objective**: Recall the basic characteristics and operation of portable fire extinguishers.

- 3-1. When a portable CO<sub>2</sub> extinguisher is not available, a portable PKP fire extinguisher can be used to extinguish a class
  - 1. ALPHA fire
  - 2. BRAVO fire
  - 3. CHARLIE fire
  - 4. DELTA fire
- 3-2. Portable PKP extinguishers come in what two sizes?
  - 1. 10 pound and 20 pound
  - 2. 12 pound and 22 pound
  - 3. 14 pound and 25 pound
  - 4. 18 pound and 27 pound
- 3-3. Because it will cake up and form a clog, you should ensure no dry chemical remains in the hose and nozzle after using which of the following extinguishers?
  - 1. Halon
  - 2. CO<sub>2</sub>
  - 3. PKP
  - 4. AFFF

- 3-4. What type of portable fire extinguisher has a stainless steel cylinder and has a 55-65 second continuous discharge time with an initial range of 15 feet?
  - 1. PKP
  - 2. Halon
  - 3. CO<sub>2</sub>
  - 4. AFFF
- 3-5. One AFFF portable fire extinguisher can vapor-seal a fuel spill of approximately what size?
  - 1. 6 feet by 6 feet
  - 2. 5 feet by 5 feet
  - 3. 3 feet by 3 feet
  - 4. 4 feet by 4 feet
- 3-6. You should never direct the spray from an AFFF portable extinguisher directly into hot cooking oil.
  - 1. True
  - 2. False
- 3-7. For approximately 40 seconds, the 15-pound CO<sub>2</sub> fire extinguisher can project a spray to what distance?
  - 1. Between 8 to 9 feet
  - 2. Between 7 to 8 feet
  - 3. Between 6 to 7 feet
  - 4. Between 4 to 6 feet

- 3-8. Before using a CO<sub>2</sub> fire extinguisher, you should take what precaution to avoid shock from static electricity?
  - 1. Release pressure by opening the safety valve
  - 2. Shake the cylinder for a few seconds
  - 3. Ground the cylinder to the deck
  - 4. Tap the cylinder with your fingers

**Learning Objective:** Recall the basic characteristics and operation of portable fire extinguishers.

- fire extinguishers.
- 3-9. What type of oxygen breathing apparatus (OBA) is used aboard most Navy ships?
  - 1. Type A-1
  - 2. Type A-2
  - 3. Type A-3
  - 4. Type A-4
- 3-10. The elements that activate the chemicals in the OBA quick-starting canister are the moisture and the
  - 1. carbon in the breastplate assembly
  - 2. citric acid in the facepiece cup
  - 3. CO<sub>2</sub> from your exhaled breath
  - 4. salt tablets in the breathing bag

- 3-11. When you are involved in hard work, the OBA canister will last for a maximum of how many minutes?
  - 1. 45
  - 2. 30
  - 3. 15
  - 4. 10
- 3-12. When you remove the cotter pin on the candle cover of an OBA canister, the candle
  - 1. is broken in half
  - 2. fires and the canister starts generating oxygen
  - 3. is pushed to the front of the canister
  - 4. is moved to the firing position
- 3-13. How often should you test the OBA facepiece for correct seal?
  - 1. Monthly
  - 2. Weekly
  - 3. After each use
  - 4. Before each use
- 3-14. To set the OBA timer, you turn the timer knob clockwise to 60 minutes and then turn it counterclockwise to 30 minutes.
  - 1. True
  - 2. False

- 3-15. The chemicals in the OBA canister can cause a violent explosion if they come into contact with
  - 1. moisture
  - 2. soap powder
  - 3. bleach solutions
  - 4. petroleum-based substances
- 3-16. The OOD may grant overboard disposal of used OBA canisters when your ship is more than how many miles from shore?
  - 1. 10
  - 2. 15
  - 3. 20
  - 4. 25
- 3-17. What environmental condition is required for the storage area for all OBA equipment and canisters?
  - 1. Hot and humid
  - 2. Cool and dry
  - 3. Hot and dry
  - 4. Cool and wet
- 3-18. The SCBA is the replacement for the OBA.
  - 1. True
  - 2. False
- 3-19. Which of the following assemblies is NOT a component of a SCBA?
  - 1. Air tank assembly
  - 2. Regulator assembly
  - 3. Canister assembly
  - 4. Facepiece assembly

- 3-20. The SAR/SCBA is designed primarily to support
  - 1. fire fighting
  - 2. gas-free testing and inspections
  - 3. radiological defense
  - 4. MOPP operations
- 3-21. One air cylinder can support a SCBA user for what maximum length of time, in minutes?
  - 1. 40
  - 2. 45
  - 3. 50
  - 4. 55
- 3-22. The fire-fighter ensemble is NOT a proximity suit. It is designed to protect a fire fighter from short duration flame exposure, heat, and falling debris.
  - 1. True
  - 2. False

**Learning Objective**: Recall the general characteristics of shipboard dewatering equipment.

- 3-23. Eductors can remove all breathing air if activated in remote spaces where ventilation is inadequate or not installed.
  - 1. True
  - 2. False

- 3-24. Before operating eductors, you must have the permission of what officer?
  - 1. OOD
  - 2. EEOW
  - 3. Executive officer
  - 4. Commanding officer

## IN ANSWERING QUESTIONS 3-25 THROUGH 3-29, REFER TO FIGURE 3A.

- A. P-100 portable emergency pump
- B. Portable submersible pump
- C. Eductors
- D. Portable AFFF in-line eductor

## Figure 3A

- 3-25. Which equipment draws water from the sea and pumps the water through hoses to supply the firemain and individual hoses?
  - 1. A
  - 2. B
  - 3. C
  - 4. D
- 3-26. Which equipment is used to mix a concentrate used to produce a solution for combating fires, especially class BRAVO fires?
  - 1. A
  - 2. B
  - 3. C
  - 4. D

- 3-27. Which equipment is designed to pump heavy oils and flammable liquids?
  - 1. A
  - 2. B
  - 3. C
  - 4. D
- 3-28. Which equipment has a 1.45-gallon fuel tank that allows a maximum of 2.75 hours of operation?
  - 1. A
  - 2. B
  - 3. C
  - 4. D
- 3-29. Which equipment should be connected directly to fire plugs to minimize inlet pressure reduction?
  - 1. A
  - 2. B
  - 3. C
  - 4. D

Learning Objective: Recall characteristics of desmoking fans and blowers and other

miscellaneous portable damage control equipment.

- 3-30. What equipment provides power to the Ramfan<sup>TM</sup> through a 1 1/2-inch connection?
  - 1. Either a portable or fixed eductor
  - 2. Either a fixed eductor or a battery
  - 3. Either the firemain or a P-100 pump
  - 4. Either a battery or a P-100 portable eductor

- 3-31. Exhausting gases through ducts can create a static electric charge.
  - 1. True
  - 2. False
- 3-32. Because the Ramfan<sup>TM</sup> produces static electricity, you must ground the ground strap before its use.
  - 1. True
  - 2. False
- 3-33. Battle lanterns are mounted in strategic locations to illuminate passageways, damage control equipment, ladders, and scuttles.
  - 1. True
  - 2. False
- 3-34. The two types of battle lanterns used on ships are identified as either relay or portable.
  - 1. True
  - 2. False

**Learning Objective**: Recall the types of firemain systems and their function.

- 3-35. How many basic types of firemain systems can be installed on naval ships?
  - 1. Five
  - 2. Two
  - 3. Three
  - 4. Six

- 3-36. What type of firemain system consists of two single fore-and-aft, cross-connected mains, installed in the same horizontal plane?
  - 1. Single main
  - 2. Horizontal loop
  - 3. Vertical loop
  - 4. Composite
- 3-37. What type of firemain system consists of two cross-connected single mains running fore and aft but separated both horizontally and vertically?
  - 1. Vertical offset loop
  - 2. Composite
  - 3. Horizontal loop
  - 4. Single main
- 3-38. The firemain system distributes water that has been pumped from the sea to fireplugs and other fire-fighting systems as required.
  - 1. True
  - 2. False

**Learning Objective**: Recall the components and operation of an installed AFFF firefighting system.

- 3-39. What other agents are used in conjunction with AFFF to fight class BRAVO fires throughout the ship?
  - 1. Halon
  - 2. Sand
  - 3. PKP
  - 4. CO

- 3-40. AFFF is delivered through installed equipment only.
  - 1. True
  - 2. False
- 3-41. AFFF systems are installed in spaces in a ship where research revealed what type of fires most often occur?
  - 1. DELTA
  - 2. CHARLIE
  - 3. BRAVO
  - 4. ALPHA
- 3-42. How many types of pumps are used with the installed AFFF system?
  - 1. One
  - 2. Two
  - 3. Three
  - 4. Four
- 3-43. The AFFF single-speed injection pump is a permanently mounted sliding-vane type of pump.
  - 1. True
  - 2. False
- 3-44. AFFF single-speed injection pumps are available in what capacities?
  - 1. 21, 24, and 32 gpm
  - 2. 18, 25, and 27 gpm
  - 3. 13, 15, and 20 gpm
  - 4. 12, 27, and 60 gpm

- 3-45. The AFFF two-speed injection pump system has a positive-displacement pump rated at what pounds per square inch (psi)?
  - 1. 100
  - 2. 125
  - 3. 150
  - 4. 175
- 3-46. The high-speed mode of the AFFF two-speed injection pump is used when flow demand exceeds what rate?
  - 1. 50 gallons per minute (gpm) for hangar bay and 75 gpm for bilge sprinklers
  - 2. 75 gpm for deck-edge sprinklers and 100 gpm for bilge sprinklers
  - 3. 150 gpm for hangar bay and deckedge sprinklers and 225 gpm for bilge sprinklers
  - 4. 250 gpm for hangar bay and deckedge sprinklers and 450 gpm for bilge sprinklers
- 3-47. AFFF transfer pumps have what maximum pumping capacity?
  - 1. 300 gpm
  - 2. 360 gpm
  - 3. 380 gpm
  - 4. 400 gpm
- 3-48. AFFF is stored in service tanks of 50to 2,000-gallon capacity and storage/ transfer tanks of up to
  - 1. 1,500-gallon capacity
  - 2. 2,000-gallon capacity
  - 3. 3,500-gallon capacity
  - 4. 4,000-gallon capacity

- 3-49. Which of the following types of valves are NOT associated with the AFFF system?
  - Powertrol, powercheck, and powertrol valve with test connection
  - 2. Hytrol, hycheck, and solenoidoperated pilot valve
  - 3. Balanced pressure proportioner (Type II), balanced pressure proportioner (Type III), and balancing valve
  - 4. Ballast and mitral
- 3-50. What type of valve protects the AFFF tank from seawater contamination or dilution?
  - 1. Powertrol
  - 2. Powercheck
  - 3. Hytrol
  - 4. Balanced pressure proportioner
- 3-51. What type of valve is normally used as a sprinkler group control valve?
  - 1. Hytrol
  - 2. Powercheck
  - 3. Powertrol with test connection
  - 4. Balanced pressure proportioner
- 3-52. What type of valve controls the flow of AFFF solution to systems?
  - 1. Hytrol
  - 2. Powercheck
  - 3. Powertrol with test connection
  - 4. Balanced pressure proportioner

- 3-53. What type of valve allows the flow of seawater from the firemain system to be mixed with AFFF concentrate?
  - 1. Hytrol
  - 2. Powercheck
  - 3. Hycheck
  - 4. Balanced pressure proportioner
- 3-54. What types of valves are electrically operated pilot valves that control the activation of many AFFF fire-extinguishing systems?
  - 1. Hytrol
  - 2. Powercheck
  - 3. Powertrol
  - 4. Solenoid Operated Pilot Valve (SOPV)
- 3-55. Which of the following types of valves automatically proportions the correct amount of AFFF concentrate with seawater?
  - 1. Hytrol
  - 2. Powercheck
  - 3. Balancing
  - 4. Powertrol
- 3-56. The balanced pressure proportioner (Type II) proportions the correct amount of AFFF concentrate necessary to produce effective AFFF/water solution over a wide range of flows and pressures.
  - 1. True
  - 2. False

- 3-57. What system provides a convenient and quick method for the fire party to apply AFFF/water solution or water to large areas of burning fuel?
  - 1. Firemain system
  - 2. AFFF sprinkler system
  - 3. Halon system
  - 4. APC system
- 3-58. What system uses the countermeasure washdown flush-deck nozzles to discharge AFFF/water solution during flight deck and helo deck fires?
  - 1. Firemain system
  - 2. AFFF sprinkler system
  - 3. Halon system
  - 4. The flush-deck system
- 3-59. The service tank of the AFFF system always contains enough concentrate to combat any large fire.
  - 1. True
  - 2. False
- 3-60. All AFFF generating station service tanks can be replenished once the transfer main is pressurized either by the reserve pump or the on-station pump.
  - 1. True
  - 2. False

- 3-61. AFFF testing equipment includes the hand refractometer and what other piece of equipment?
  - 1. Spectrograph
  - 2. Reflex condenser
  - 3. M-8 paper
  - 4. Quantab chloride titrator strip
- 3-62. What instrument gives accurate readings of total dissolved solids in aqueous solutions?
  - 1. Spectrograph
  - 2. Hand refractometer
  - 3. Reflex condenser
  - 4. Spectrometer
- 3-63. After taking hand refractometer readings, you can determine the percent of AFFF concentrate that is being proportioned with water by using the following formula:

$$\frac{A}{R}$$
 x 100 = % of AFFF concentrate

- 1. True
- 2. False
- 3-64. Quantab chloride titrator strips are used to measure what chemical compound in aqueous solutions?
  - 1. Sodium hydroxide
  - 2. Sulfuric acid
  - 3. Sodium chloride (salt)
  - 4. Potassium cyanide

- 3-65. The allowable limit for chloride contamination of AFFF concentrate is 2,000 ppm, which equates to what percent contamination?
  - 1. 10
  - 2. 20
  - 3. 30
  - 4. 40
- 3-66. There are how many types of installed CO<sub>2</sub> flooding systems?
  - 1. One
  - 2. Two
  - 3. Three
  - 4. Four
- 3-67. You should always direct the CO<sub>2</sub> discharge
  - 1. at the base of a fire
  - 2. at the middle of a fire
  - 3. at the top of a fire
  - 4. above a fire
- 3-68. The number of valve control devices provided for a CO<sub>2</sub> flooding system depends upon the number of cylinders in the bank.
  - 1. True
  - 2. False

- 3-69. Aboard aircraft carriers, what type of fire extinguishing system is normally installed in the gas-powered bomb hoist storerooms?
  - 1. Firemain system
  - 2. AFFF sprinkler system
  - 3. Halon 1301 system
  - 4. Flush-deck system
- 3-70. Sufficient Halon is required so the concentration will remain at a minimum of 5 percent for how many minutes?
  - 1. 45
  - 2. 30
  - 3. 15
  - 4. 10
- 3-71. Each Halon fixed-flooding system is designed to discharge completely the Halon 1301 gas into the protected space within how many seconds?
  - 1. 40
  - 2. 30
  - 3. 20
  - 4. 10
- 3-72. What fire-extinguishing system provides protection for galley deepfat and doughnut fryers and their exhaust systems?
  - 1. APC
  - 2. PKP
  - 3. Halon 1301
  - 4. Installed CO<sub>2</sub>